

View Online at <https://aerobasegroup.com/nsn/5915-01-200-3661>

Overall Length:

1.138 inches

Body Length:

0.758 inches

Body Outside Diameter:

0.406 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.088 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

1000.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

5.0 blank

Maximum Voltage Drop Per Function:

1.5 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.15 and 0.3 and 1.0 and 10.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

3.0 and 5.0 and 25.0 and 59.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

150.0 volts dc blank

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

750.0 volts at sea level

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

8.5 grams

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0