

View Online at <https://aerobasegroup.com/nsn/5915-01-210-1759>

Overall Height:

0.900 inches

Body Length:

2.500 inches

Body Width:

1.250 inches

Body Height:

0.650 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.188 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

Average Life Rating In Hours:

20000.0

Reference Frequency Per Function:

500.0 kilohertz blank all functions

Source Impedance Rating Per Function:

1.0 kilohms blank all functions

Load Impedance Per Function:

1.0 kilohms blank all functions

Principal Circuitry Type Per Function:

Crystal blank all functions

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole all functions

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank all functions

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

492.0 megahertz blank and 498.80 megahertz blank and 501.20 megahertz blank and 508.0 megahertz blank all functions

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

498.80 megahertz blank and 501.20 megahertz blank all functions

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank all functions

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0