

View Online at <https://aerobasegroup.com/nsn/5915-01-217-4082>

Overall Height:

4.601 inches

Body Length:

3.031 inches

Body Width:

2.031 inches

Body Height:

3.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-40.0 to 85.0 degrees celsius

End Application:

Tsttu-205/d

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference 2nd function

Load Impedance Per Function:

50.0 ohms 2nd radio interference 2nd function

Power Line Frequency Rating Per Function In Hertz:

420.0 2nd radio interference 2nd function

Operating Current Rating Per Function In Amps:

10.0 2nd radio interference 2nd function

Maximum Voltage Drop Per Function:

1.0 volts ac 2nd radio interference 2nd function

Principal Circuitry Type Per Function:

Capacitance-inductance 2nd radio interference 2nd function

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms3436a-20-4s

Maximum Temperature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole all functions

Functional Terminal Type And Quantity:

2 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

126.5 volts ac 2nd radio interference 2nd function

Thread Size:

0.164 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

800.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0