

View Online at <https://aerobasegroup.com/nsn/5915-01-217-4082>

**Overall Height:**

4.601 inches

**Body Length:**

3.031 inches

**Body Width:**

2.031 inches

**Body Height:**

3.031 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Operating Temperature Range:**

-40.0 to 85.0 degrees celsius

**End Application:**

Tsttu-205/d

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference 2nd function

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference 2nd function

**Power Line Frequency Rating Per Function In Hertz:**

420.0 2nd radio interference 2nd function

**Operating Current Rating Per Function In Amps:**

10.0 2nd radio interference 2nd function

**Maximum Voltage Drop Per Function:**

1.0 volts ac 2nd radio interference 2nd function

**Principal Circuitry Type Per Function:**

Capacitance-inductance 2nd radio interference 2nd function

**Input Terminal Manufacturer Code:**

96906

**Input Terminal Identification:**

Ms3436a-20-4s

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole all functions

**Functional Terminal Type And Quantity:**

2 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

126.5 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

800.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0