NSN 5915-01-220-1641

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-220-1641

Overall Length:
6.750 inches
Overall Height:
4.130 inches
Body Length:
4.500 inches
Body Width:
9.500 inches
Body Height:
3.380 inches
Unthreaded Mounting Hole Diameter:
0.218 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
6.150 inches
Vibration Resistance Range In Hertz:
+10.0 to 500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
10.400 inches
Operating Tempurature Range:
-55.0 to 85.0 degrees celsius
End Application:
Communications control center an/tsq-11 ()(v)
Source Impedance Rating Per Function:
50.0 ohms 2nd radio interference 2nd function
Load Impedance Per Function:
50.0 ohms 2nd radio interference 2nd function
Power Line Frequency Rating Per Function In Hertz:
60.0 2nd radio interference 2nd function
Operating Current Rating Per Function In Amps:
30.0 1st radio interference 1st function
Maximum Voltage Drop Per Function:
1.25 volts ac 2nd radio interference 2nd function
Principal Circuitry Type Per Function:
Inductance-capacitance 2nd radio interference 2nd function
Input Terminal Manufacturer Code:
96906
Input Terminal Identification:
Ms3450w16-10p
Inclosure Type:
Hermetically sealed

14 unthreaded hole 1st function

Mounting Facility Type And Quantity:

NSN 5915-01-220-1641

Radio Frequency Interference Filter - Page 2 of 2



Functional Terminal Type And Quantity:

2 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

125.0 volts ac 1st radio interference 1st function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Unpackaged Unit Weight:

14.500 pounds

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0