## NSN 5915-01-222-0878

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-222-0878

| Overall Length:  |
|--|
| 5.120 inches   |
| Body Length:   |
| 3.520 inches   |
| Body Width:  |
| 6.750 inches   |
| Body Height:   |
| 3.120 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.219 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 4.500 inches   |
| Vibration Resistance Range In Hertz:   |
| +10.0 to 500.0   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:  |
| 5.000 inches   |
| Operating Tempurature Range:   |
| -55.0 to 105.0 degrees celsius   |
| End Application:   |
| Communication c an/tsq-111   |
| Source Impedance Rating Per Function:  |
| 50.0 ohms 2nd radio interference 2nd function                                |
| Load Impedance Per Function:   |
| 50.0 ohms 2nd radio interference 2nd function                                |
| Power Line Frequency Rating Per Function In Hertz:                           |
| 410.0 2nd radio interference 2nd function                                    |
| Operating Current Rating Per Function In Amps:                               |
| 7.0 2nd radio interference 2nd function                                      |
| Maximum Voltage Drop Per Function:   |
| 0.75 volts ac 2nd radio interference 2nd function                            |
| Input Terminal Manufacturer Code:  |
| 96906  |
| Input Terminal Identification:   |
| Ms3474I-12-3p  |
| Inclosure Type:  |
| Encased  |
| Mounting Facility Type And Quantity:   |
| 6 unthreaded hole 1st function   |
| Functional Terminal Type And Quantity:                                       |
| 2 threaded stud output 2nd function  |

Operating Voltage Rating And Type Per Function: 130.0 volts ac 2nd radio interference 2nd function

## NSN 5915-01-222-0878

Radio Frequency Interference Filter - Page 2 of 2



| Body Material:                                      |
|---|
| Metal   |
| Maximum Dielectric Withstanding Dc Voltage:         |
| 500.0 volts at sea level                            |
| Body Surface Treatment:                             |
| Tin   |
| Style Designator:                                   |
| Rectangular terminal/terminals on opposite surfaces |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| Yes - demil/mli                                     |
| Fiig:   |

A047b0