

View Online at <https://aerobasegroup.com/nsn/5915-01-222-3594>

Overall Height:

Between 1.115 inches and 1.145 inches

Body Length:

Between 2.365 inches and 2.395 inches

Body Width:

Between 0.985 inches and 1.015 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.930 inches and 1.944 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.555 inches and 0.569 inches

Operating Temperature Range:

-30.0 to 75.0 degrees celsius

End Application:

5895-01-160-0482 preselector assembly

Reference Frequency Per Function:

21.4 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Features Provided:

Shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

20.90 megahertz blank and 21.25 megahertz blank and 21.55 megahertz blank and 21.90 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

21.25 megahertz blank and 21.55 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0