

View Online at <https://aerobasegroup.com/nsn/5915-01-223-3473>

**Overall Height:**

0.875 inches

**Body Length:**

Between 1.485 inches and 1.515 inches

**Body Width:**

Between 0.985 inches and 1.015 inches

**Body Height:**

Between 0.485 inches and 0.515 inches

**Vibration Resistance Range In Hertz:**

+5.0 to 200.0

**Operating Temperature Range:**

-35.0 to 85.0 degrees celsius

**End Application:**

5895-01-180-1415 control, computer

**Reference Frequency Per Function:**

21.4 megahertz blank all functions

**Source Impedance Rating Per Function:**

50.0 ohms blank all functions

**Load Impedance Per Function:**

50.0 ohms blank all functions

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank all functions

**Voltage Standing Wave Ratio Per Function:**

2.0 blank all functions

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 terminal all functions

**Features Provided:**

Shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.2 blank all functions

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

20.76 megahertz blank and 21.08 megahertz blank and 21.72 megahertz blank and 22.04 megahertz blank all functions

**Body Material:**

Metal

**Frequency Band Width Per Function:**

21.08 megahertz blank and 21.72 megahertz blank all functions

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 40.0 blank all functions

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

21.08 megahertz blank and 21.72 megahertz blank all functions

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0