

View Online at <https://aerobasegroup.com/nsn/5915-01-226-2010>

**Overall Height:**

1.500 inches

**Body Length:**

3.200 inches

**Body Width:**

1.250 inches

**Body Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.600 inches

**Vibration Resistance Range In Hertz:**

+4.0 to 50.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.562 inches

**Reference Frequency Per Function:**

1.65 megahertz blank all functions

**Source Impedance Rating Per Function:**

50.0 ohms blank all functions

**Load Impedance Per Function:**

50.0 ohms blank all functions

**Voltage Standing Wave Ratio Per Function:**

1.5 blank all functions

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud all functions

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank all functions

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.6484 megahertz blank and 1.6493 megahertz blank and 1.6507 megahertz blank and 1.6516 megahertz blank all functions

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.6493 megahertz blank and 1.6507 megahertz blank all functions

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank all functions

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.6493 megahertz blank and 1.6507 megahertz blank all functions

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0