

View Online at <https://aerobasegroup.com/nsn/5915-01-226-2010>

Overall Height:

1.500 inches

Body Length:

3.200 inches

Body Width:

1.250 inches

Body Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.600 inches

Vibration Resistance Range In Hertz:

+4.0 to 50.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

Reference Frequency Per Function:

1.65 megahertz blank all functions

Source Impedance Rating Per Function:

50.0 ohms blank all functions

Load Impedance Per Function:

50.0 ohms blank all functions

Voltage Standing Wave Ratio Per Function:

1.5 blank all functions

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud all functions

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank all functions

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.6484 megahertz blank and 1.6493 megahertz blank and 1.6507 megahertz blank and 1.6516 megahertz blank all functions

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.6493 megahertz blank and 1.6507 megahertz blank all functions

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank all functions

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.6493 megahertz blank and 1.6507 megahertz blank all functions

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0