## NSN 5915-01-226-2011

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-226-2011

Overall Height:
1.500 inches
Body Length:
3.200 inches
Body Width:
1.250 inches
Body Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.600 inches
Vibration Resistance Range In Hertz:
+4.0 to 50.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Reference Frequency Per Function:
1.65 megahertz blank all functions
Source Impedance Rating Per Function:
50.0 ohms blank all functions
Load Impedance Per Function:
50.0 ohms blank all functions
Voltage Standing Wave Ratio Per Function:
1.5 blank all functions
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded stud all functions
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank all functions
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.6468 megahertz blank and 1.6486 megahertz blank and 1.6514 megahertz blank and 1.6532 megahertz blank all functions
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
1.6486 megahertz blank and 1.6514 megahertz blank all functions

60.0 blank and 3.0 blank and 60.0 blank all functions

Discrimination At Specificationified Frequencies Per Function In Decibels:

## NSN 5915-01-226-2011

Band Pass Filter - Page 2 of 2



Voltage	Standing	<b>Wave Ratio</b>	Frequency	I imits Per	Function:
vollaue	Staniumu	Wave nauc	rieduelicv	LIIIIII TEI	FullCuoii.

1.6486 megahertz blank and 1.6514 megahertz blank all functions

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0