## NSN 5915-01-226-2012

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-226-2012

Overall Height:
1.500 inches
Body Length:
3.200 inches
Body Width:
1.250 inches
Body Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.600 inches
Vibration Resistance Range In Hertz:
+4.0 to 50.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Operating Tempurature Range:
-0.0 to 60.0 degrees celsius
Reference Frequency Per Function:
1.65 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.6425 megahertz blank and 1.64675 megahertz blank and 1.65325 megahertz blank and 1.6575 megahertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:

1.64675 megahertz blank and 1.65325 megahertz blank

## NSN 5915-01-226-2012

Band Pass Filter - Page 2 of 2



Discrimination At Speci	ficationified Fred	quencies Per Fr	unction In De	cibels:
-------------------------	--------------------	-----------------	---------------	---------

50.0 blank and 3.0 blank and 50.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:** 

1.64675 megahertz blank and 1.65325 megahertz blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A047b0