

View Online at <https://aerobasegroup.com/nsn/5915-01-227-8524>

Overall Height:

0.520 inches

Body Length:

2.000 inches

Body Width:

0.390 inches

Body Height:

0.400 inches

Unthreaded Mounting Hole Diameter:

0.090 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.240 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

150.0 megahertz blank all functions

Source Impedance Rating Per Function:

50.0 ohms blank all functions

Load Impedance Per Function:

50.0 ohms blank all functions

Principal Circuitry Type Per Function:

Inductance-capacitance blank all functions

Voltage Standing Wave Ratio Per Function:

1.5 blank all functions

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole all functions

Features Provided:

Fungus resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

1.5 blank all functions

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

100.00 megahertz blank and 125.00 megahertz blank and 175.00 megahertz blank and 200.00 megahertz blank all functions

Body Material:

Aluminum

Frequency Band Width Per Function:

125.00 megahertz blank and 175.00 megahertz blank all functions

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 27.0 blank all functions

Voltage Standing Wave Ratio Frequency Limits Per Function:

125.0 megahertz blank and 175.0 megahertz blank all functions

Body Surface Treatment:

Cadmium

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0