

View Online at <https://aerobasegroup.com/nsn/5915-01-228-6607>

Overall Length:

2.680 inches

Overall Height:

2.187 inches

Body Length:

2.500 inches

Body Width:

2.000 inches

Body Height:

1.500 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference 2nd function

Load Impedance Per Function:

50.0 ohms 2nd radio interference 2nd function

Power Line Frequency Rating Per Function In Hertz:

60.0 2nd radio interference 2nd function

Operating Current Rating Per Function In Amps:

5.0 2nd radio interference 2nd function

Maximum Voltage Drop Per Function:

2.3 volts ac 2nd radio interference 2nd function

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference 2nd function

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.15 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

3.0 and 40.0 and 80.0 and 80.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud all functions

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

230.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.138 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

460.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0