

View Online at <https://aerobasegroup.com/nsn/5915-01-228-6607>

**Overall Length:**

2.680 inches

**Overall Height:**

2.187 inches

**Body Length:**

2.500 inches

**Body Width:**

2.000 inches

**Body Height:**

1.500 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference 2nd function

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference 2nd function

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference 2nd function

**Operating Current Rating Per Function In Amps:**

5.0 2nd radio interference 2nd function

**Maximum Voltage Drop Per Function:**

2.3 volts ac 2nd radio interference 2nd function

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference 2nd function

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.15 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

3.0 and 40.0 and 80.0 and 80.0 and 80.0 and 80.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud all functions

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

230.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

460.0 volts at sea level

**Special Features:**

Two filtered functions

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0