

View Online at <https://aerobasegroup.com/nsn/5915-01-229-1432>

Overall Length:

4.300 inches

Body Width:

0.380 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.235 inches

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

19.0 megahertz blank all functions

Source Impedance Rating Per Function:

50.0 ohms blank all functions

Load Impedance Per Function:

50.0 ohms blank all functions

Input Terminal Manufacturer Code:

00752

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

00752

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank all functions

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole all functions

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank all functions

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

250.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

160.0 megahertz blank and 184.5 megahertz blank and 195.5 megahertz blank and 220.0 megahertz blank all functions

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

184.5 megahertz blank and 195.5 megahertz blank all functions

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank all functions

Voltage Standing Wave Ratio Frequency Limits Per Function:

184.5 megahertz blank and 195.5 megahertz blank all functions

Unpackaged Unit Weight:

2.500 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0