

View Online at <https://aerobasegroup.com/nsn/5915-01-230-2929>

Overall Length:

3.650 inches

Body Length:

3.400 inches

Body Width:

2.050 inches

Body Height:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.900 inches

Vibration Resistance Range In Hertz:

+5.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.600 inches

Operating Temperature Range:

-5.0 to 75.0 degrees celsius

Reference Frequency Per Function:

340.5 kilohertz 2nd band pass 2nd function

Source Impedance Rating Per Function:

1.0 kilohms 1st band pass 1st function

Load Impedance Per Function:

1.0 kilohms 2nd band pass 2nd function

Principal Circuitry Type Per Function:

Crystal 2nd band pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole all functions

Insertion Loss At Reference Frequency Per Function In Decibels:

4.5 2nd band pass 2nd function

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

310.50 kilohertz 2nd band pass and 339.50 kilohertz 2nd band pass and 341.50 kilohertz 2nd band pass and 380.50 kilohertz 2nd band pass 2nd function

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

339.50 kilohertz 1st band pass and 341.50 kilohertz 1st band pass 1st function

Discrimination At Specificationified Frequencies Per Function In Decibels:

55.0 2nd band pass and 3.0 2nd band pass and 3.0 2nd band pass and 55.0 2nd band pass 2nd function

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0