

View Online at <https://aerobasegroup.com/nsn/5915-01-230-2929>

**Overall Length:**

3.650 inches

**Body Length:**

3.400 inches

**Body Width:**

2.050 inches

**Body Height:**

0.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.900 inches

**Vibration Resistance Range In Hertz:**

+5.0 to 500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.600 inches

**Operating Temperature Range:**

-5.0 to 75.0 degrees celsius

**Reference Frequency Per Function:**

340.5 kilohertz 2nd band pass 2nd function

**Source Impedance Rating Per Function:**

1.0 kilohms 1st band pass 1st function

**Load Impedance Per Function:**

1.0 kilohms 2nd band pass 2nd function

**Principal Circuitry Type Per Function:**

Crystal 2nd band pass 2nd function

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole all functions

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.5 2nd band pass 2nd function

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

310.50 kilohertz 2nd band pass and 339.50 kilohertz 2nd band pass and 341.50 kilohertz 2nd band pass and 380.50 kilohertz 2nd band pass 2nd function

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

339.50 kilohertz 1st band pass and 341.50 kilohertz 1st band pass 1st function

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

55.0 2nd band pass and 3.0 2nd band pass and 3.0 2nd band pass and 55.0 2nd band pass 2nd function

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0