

View Online at <https://aerobasegroup.com/nsn/5915-01-230-4513>

Overall Length:

4.762 inches

Body Outside Diameter:

0.185 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

End Application:

Receiving set, countermeasures an/alr-56c

Reference Frequency Per Function:

580.0 megahertz blank all functions

Source Impedance Rating Per Function:

50.0 ohms blank all functions

Load Impedance Per Function:

50.0 ohms blank all functions

Input Terminal Manufacturer Code:

81413

Input Terminal Identification:

Sma-plug

Output Terminal Manufacturer Code:

81413

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank all functions

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal all functions

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank all functions

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.16 gigahertz blank and 2.01 gigahertz blank and 8.50 gigahertz blank all functions

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 1.16 gigahertz blank all functions

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank all functions

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 1.16 gigahertz blank all functions

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

0.470 ounces

Precious Material And Location:

Center conductor silver

Precious Material:

Silver

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0