

View Online at <https://aerobasegroup.com/nsn/5915-01-230-4513>

**Overall Length:**

4.762 inches

**Body Outside Diameter:**

0.185 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 500.0

**End Application:**

Receiving set, countermeasures an/alr-56c

**Reference Frequency Per Function:**

580.0 megahertz blank all functions

**Source Impedance Rating Per Function:**

50.0 ohms blank all functions

**Load Impedance Per Function:**

50.0 ohms blank all functions

**Input Terminal Manufacturer Code:**

81413

**Input Terminal Identification:**

Sma-plug

**Output Terminal Manufacturer Code:**

81413

**Output Terminal Identification:**

Sma-receptacle

**Voltage Standing Wave Ratio Per Function:**

1.5 blank all functions

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal all functions

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank all functions

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 1.16 gigahertz blank and 2.01 gigahertz blank and 8.50 gigahertz blank all functions

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 1.16 gigahertz blank all functions

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank all functions

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 hertz blank and 1.16 gigahertz blank all functions

**Body Surface Treatment:**

Tin

**Unpackaged Unit Weight:**

0.470 ounces

**Precious Material And Location:**

Center conductor silver

**Precious Material:**

Silver

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0