

View Online at <https://aerobasegroup.com/nsn/5915-01-233-3159>

**Overall Height:**

2.935 inches

**Body Length:**

4.500 inches

**Body Width:**

3.500 inches

**Body Height:**

1.620 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.875 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.875 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 3rd radio interference 3rd function

**Load Impedance Per Function:**

50.0 ohms 4th radio interference 4th function

**Power Line Frequency Rating Per Function In Hertz:**

400.0 4th radio interference 4th function

**Operating Current Rating Per Function In Amps:**

7.0 2nd radio interference 2nd function

**Maximum Voltage Drop Per Function:**

1.15 volts ac 4th radio interference 4th function

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference 3rd function

**Input Terminal Manufacturer Code:**

23939

**Input Terminal Identification:**

Ms3454w18-11p

**Maximum Temperature Rise:**

85.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole all functions

**Functional Terminal Type And Quantity:**

4 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 4th radio interference 4th function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

230.0 volts at sea level

**Special Features:**

Four filtered functions

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0