

View Online at <https://aerobasegroup.com/nsn/5915-01-235-4032>

Overall Height:

4.000 inches

Body Length:

5.120 inches

Body Width:

2.000 inches

Body Height:

3.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.125 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.500 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference 60.0 3rd radio interference 60.0 4th radio interference 60.0 5th radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference 3.0 2nd radio interference 3.0 3rd radio interference 3.0 4th radio interference 3.0 5th radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 1st radio interference 1.15 volts ac 2nd radio interference 1.15 volts ac 3rd radio interference 1.15 volts ac 4th radio interference 1.15 volts ac 5th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Functional Terminal Type And Quantity:

5 screw input 1st function 5 screw output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function 115.0 volts ac 2nd radio interference 2nd function 115.0 volts ac 3rd radio interference 3rd function 115.0 volts ac 4th radio interference 4th function 115.0 volts ac 5th radio interference 5th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

230.0 volts at sea level

Special Features:

Five filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0