

View Online at <https://aerobasegroup.com/nsn/5915-01-235-6230>

Overall Length:

3.320 inches

Body Length:

2.560 inches

Body Width:

2.560 inches

Body Height:

1.330 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.188 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.188 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

2.0 1st radio interference 2.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.26 volts ac 1st radio interference 1.26 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Functional Terminal Type And Quantity:

2 tab, solder lug input 1st function 2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

126.0 volts ac 1st radio interference 1st function 126.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.138 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0