NSN 5915-01-236-9252

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-236-9252

| Overall Length: |
|---|
| 12.375 inches |
| Overall Height: |
| 4.438 inches |
| Overall Width: |
| 26.500 inches |
| Body Length: |
| 10.375 inches |
| Body Width: |
| 14.500 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.375 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 11.375 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+55.0 |
| Average Life Rating In Hours: |
| 250.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms 2nd radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 2nd radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 400.0 2nd radio interference |
| Operating Current Rating Per Function In Amps: |
| 20.0 2nd radio interference |
| Maximum Tempurature Rise: |
| 25.0 degrees celsius |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Functional Terminal Type And Quantity: |
| 2 threaded stud input 1st function |
| Operating Voltage Rating And Type Per Function: |
| 277.0 volts ac 1st radio interference 1st function and 600.0 volts dc 1st radio interference 1st function |
| Body Material: |
| Metal |
| Maximum Dielectric Withstanding Dc Voltage: |
| 1.2 kilovolts at sea level |
| Style Designator: |

Rectangular terminal/terminals on opposite surfaces

NSN 5915-01-236-9252

Radio Frequency Interference Filter - Page 2 of 2



| Shelf | Lite: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0