

View Online at <https://aerobasegroup.com/nsn/5915-01-242-2452>

Body Length:

2.440 inches

Body Width:

0.700 inches

Body Height:

0.700 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-10.0/+50.0 degrees celsius

End Application:

Test set, countermeasures set an/alm-233

Reference Frequency Per Function:

6.0 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

63132

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

63132

Output Terminal Identification:

Sma-connector

Voltage Standing Wave Ratio Per Function:

2.0 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

3.40 gigahertz blank and 4.00 gigahertz blank and 8.00 gigahertz blank and 9.20 gigahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

4.00 gigahertz blank and 8.00 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

4.0 gigahertz blank and 8.0 gigahertz blank

Body Surface Treatment:

Silver

Precious Material And Location:

Body surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0