NSN 5915-01-247-3039

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-247-3039

Body Length:
1.900 inches
Body Width:
1.650 inches
Body Height:
1.150 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.150 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.900 inches
Operating Tempurature Range:
-54.0/+71.0 degrees celsius
Reference Frequency Per Function:
1.835 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Input Terminal Manufacturer Code:
94987
Input Terminal Identification:
Sma-receptacle
Output Terminal Manufacturer Code:
94987
Output Terminal Identification:
Sma-receptacle
Voltage Standing Wave Ratio Per Function:
1.25 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Features Provided:

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

NSN 5915-01-247-3039

Low Pass Filter - Page 2 of 2



1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.825 gigahertz blank and 1.845 gigahertz blank and 1.9798 gigahertz blank and 1.9998 gigahertz blank

Th	rea	Ы	S	iz	Δ.	

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.825 gigahertz blank and 1.845 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 30.0 blank and 30.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.825 gigahertz blank and 1.845 gigahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0