NSN 5915-01-248-7165

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-248-7165

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Average Life Rating In Hours:

1000.0

End Application:

Mk73mod5, 6 di

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Operating Current Rating Per Function In Amps:

5.0 3rd radio interference

Maximum Voltage Drop Per Function:

0.075 volts dc 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Input Terminal Manufacturer Code:

81349

Input Terminal Identification:

M24308/4-3

Output Terminal Manufacturer Code:

81349

Output Terminal Identification:

M24308/2-3

Maximum Tempurature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 termina

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function

Operating Voltage Rating And Type Per Function:

100.0 volts dc 6th radio interference 6th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

250.0 volts at sea level

Special Features:

Twenty filtered functions

NSN 5915-01-248-7165

Radio Frequency Interference Filter - Page 2 of 2



Style	Des	ian	ato	r:
,				

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0