

View Online at <https://aerobasegroup.com/nsn/5915-01-248-7165>

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**End Application:**

Mk73mod5, 6 di

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 5th radio interference

**Operating Current Rating Per Function In Amps:**

5.0 3rd radio interference

**Maximum Voltage Drop Per Function:**

0.075 volts dc 6th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 6th radio interference

**Input Terminal Manufacturer Code:**

81349

**Input Terminal Identification:**

M24308/4-3

**Output Terminal Manufacturer Code:**

81349

**Output Terminal Identification:**

M24308/2-3

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function

**Operating Voltage Rating And Type Per Function:**

100.0 volts dc 6th radio interference 6th function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

250.0 volts at sea level

**Special Features:**

Twenty filtered functions

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0