

View Online at https://aerobasegroup.com/nsn/5915-01-249-9102

Overall Length: 4.000 inches Body Length: 2.875 inches Body Width: 2.438 inches Body Height: 1.875 inches Body Height: 1.875 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 4000.0 2nd radio interference Power Line Frequency Rating Per Function In Amps: 2.0.1 st radio interference Porting Current Rating Per Function In Amps: 2.0 1 st radio interference Poincipal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Incosure Type: Encased Mounting Facility Type And Quantity: 7 threade stud output 2nd function Choiets ac 2nd radio interference 2nd function	
Body Length: 2.875 inches Body Width: 2.438 inches Body Height: 1.875 inches Vibration Resistance Range In Hertz: +10.0/+200.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.90 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Poreating Current Rating Per Function In Amps: 2.0.1 str adio interference Poincipal Circuitry Type Per Function In Amps: 2.0.1 str adio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Horead Size: 0.164 inches	Overall Length:
2.875 inches Body Width: 2.438 inches Body Height: 1.875 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Hower Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Power Line Frequency Rating Per Function In Amps: 2.0.1 st radio interference Poincipal Circuitry Type Per Function In Amps: 2.0.1 st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Moreading Voltage Rating And Type Per Function: 115.0 volts a c2nd radio interference 2nd function Houted hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function	
Body Width:2.438 inchesBody Height:1.875 inchesVibration Resistance Range In Hertz:+10.0/+2000.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:1.190 inchesOperating Tempurature Range:-20.0/+55.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceHoude InterferencePower Line Frequency Rating Per Function In Hertz:20.0 />0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:20.0 zond radio interferencePower Line Frequency Rating Per Function In Hertz:20.0 zond radio interferencePourting Current Rating Per Function In Amps:20.1 st radio interferencePounting Facility Spee Per function:Inductance-capacitance 2nd radio interferenceMounting Facility Spee Mitherad Series Designator:UrcIncasedMounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:15.0 volts ac 2nd radio interference 2nd function15.0 volts ac 2nd radio interference 2nd function16.0 volts ac 2nd radio interference 2nd function16.0 volts ac 2nd radio interference	
2.438 inches Body Height: 1.875 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Hower Line Frequency Rating Per Function In Hertz: 4000 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 4000 2nd radio interference Porting Current Rating Per Function In Amps: 2.0 1 st radio interference Porting Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Urc Incased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function 15.0 volts ac 2nd radio interference 2nd function 17.0 volts ac 2nd radio interference 2nd function 17.0 volts ac 2nd radio interference 2nd function 17.0 volts ac 2nd radio interference 2nd function	2.875 inches
Body Heigh: 1.875 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 20.1 st radio interference Poincipal Circuitry Type Per Function In Amps: 2.0 1 st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size:	Body Width:
1.875 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Porting Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Other Size: 0.164 inches	
Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 15.0 volts ac 2nd radio interference 2nd function Ints.0 volts ac 2nd radio interference 2nd function Coreating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Coreating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Chreaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Chread Size: 0.164 inches Body Material:	Body Height:
+10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1 st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 15.0 volts ac 2nd radio interference 2nd function Introjous ac 2nd radio interference 2nd function Charding Voltage Rating And Type Per Function: 10.15.0 volts ac 2nd radio interference 2nd function Charding Facility Screw Thread Cuantity: 2 threaded stud output 2nd function Charding Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Charding Screw Thread Series Designator: 2 threaded stud output 2nd function Contractional Terminal Type And Quantity: 2 threaded stud output 2nd function Charding Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Charding Size: 0.164 inches Body Material:	1.875 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inductance-capacitance 2nd radio interference Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Vibration Resistance Range In Hertz:
1.190 inches Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	+10.0/+2000.0
Operating Tempurature Range: -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
 -20.0/+55.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material: 	1.190 inches
Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Mounting Facility Corew Thread Series Designator: 115.0 volts ac 2nd radio interference 2nd function: 115.0 volts ac 2nd radio interference 2nd function Chread Size: 0.164 inches Body Material:	Operating Tempurature Range:
50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 2nd radio interferenceOperating Current Rating Per Function In Amps:2.0 1st radio interferencePrincipal Circuitry Type Per Function:Inductance-capacitance 2nd radio interferenceMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:2 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 2nd radio interference 2nd functionThread Size:0.164 inchesBody Material:	-20.0/+55.0 degrees celsius
Load Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 2nd radio interferenceOperating Current Rating Per Function In Amps:2.0 1st radio interferencePrincipal Circuitry Type Per Function:Inductance-capacitance 2nd radio interferenceMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:2 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 2nd radio interference 2nd functionThread Size:0.164 inchesBody Material:	Source Impedance Rating Per Function:
50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	50.0 ohms 2nd radio interference
Power Line Frequency Rating Per Function In Hertz:400.0 2nd radio interferenceOperating Current Rating Per Function In Amps:2.0 1st radio interferencePrincipal Circuitry Type Per Function:Inductance-capacitance 2nd radio interferenceMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:2 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 2nd radio interference 2nd functionThread Size:0.164 inchesBody Material:	Load Impedance Per Function:
400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	50.0 ohms 2nd radio interference
Operating Current Rating Per Function In Amps:2.0 1st radio interferencePrincipal Circuitry Type Per Function:Inductance-capacitance 2nd radio interferenceMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:2 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 2nd radio interference 2nd functionThread Size:0.164 inchesBody Material:	Power Line Frequency Rating Per Function In Hertz:
 2.0 1st radio interference Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material: 	400.0 2nd radio interference
Principal Circuitry Type Per Function: Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Operating Current Rating Per Function In Amps:
Inductance-capacitance 2nd radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	2.0 1st radio interference
Mounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:2 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 2nd radio interference 2nd functionThread Size:0.164 inchesBody Material:	Principal Circuitry Type Per Function:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Inductance-capacitance 2nd radio interference
Inclosure Type: Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Mounting Facility Screw Thread Series Designator:
Encased Mounting Facility Type And Quantity: 7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Unc
Mounting Facility Type And Quantity:7 threaded holeFunctional Terminal Type And Quantity:2 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 2nd radio interference 2nd functionThread Size:0.164 inchesBody Material:	Inclosure Type:
7 threaded hole Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Encased
 Functional Terminal Type And Quantity: 2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material: 	Mounting Facility Type And Quantity:
2 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	7 threaded hole
Operating Voltage Rating And Type Per Function: 115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	Functional Terminal Type And Quantity:
115.0 volts ac 2nd radio interference 2nd function Thread Size: 0.164 inches Body Material:	2 threaded stud output 2nd function
Thread Size: 0.164 inches Body Material:	Operating Voltage Rating And Type Per Function:
0.164 inches Body Material:	115.0 volts ac 2nd radio interference 2nd function
Body Material:	Thread Size:
-	0.164 inches
Metal	Body Material:
	Metal
Style Designator:	Style Designator:
Rectangular terminal/terminals on opposite surfaces	Rectangular terminal/terminals on opposite surfaces
Shelf Life:	Shelf Life:
N/a	N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0