

View Online at https://aerobasegroup.com/nsn/5915-01-249-9686

Overall Length:1.547 inchesBody Length:1.020 inchesBody Outside Diameter:0.375 inchesVibration Resistance Range In Hertz:+10.0/+2000.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:0.25 blankPoure Inde Frequency Rating Per Function In Amps:0.25 blankPoure Line Frequency Rating Per Function In Amps:0.25 blankPoureing Current Rating Per Function In Amps:0.25 blankPincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 300.0 volts dc blankThread Size:0.250 inchesBody Material:MetalMaximum Dielectric Withstanding Dc Voltage:600.0 volts at sea levelStyle Designator:NaViaMetalMaximum Dielectric Withstanding Dc Voltage:600.0 volts at sea levelStyle Designato	
Body Length:         1.020 inches         Body Outside Diameter:         0.375 inches         Vibration Resistance Range In Hertz:         +10.0/+2000.0         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Power Line Frequency Rating Per Function In Hertz:         400.0 blank         Operating Current Rating Per Function In Amps:         0.25 blank         Principal Circuitry Type Per Function In Amps:         0.25 blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         15.0 volts ac blank and 300.0 volts dc blank         Thread Size:         0.250 inches         Body Material:         Metal         Maximum Dielectric Withstanding Dc Voltage:         600.0 volts at sea level <td>Overall Length:</td>	Overall Length:
1.020 inches Body Outside Diameter: 0.375 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Load Impedance Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Hertz: 400.0 blank Principal Circuitry Type Per Function In Amps: 0.25 blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 15.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: Gou.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	1.547 inches
Body Outside Diameter:         0.375 inches         Vibration Resistance Range In Hertz:         +10.0/+2000.0         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Power Line Frequency Rating Per Function In Hertz:         400.0 blank         Operating Current Rating Per Function In Amps:         0.25 blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         15.0 volts ac blank and 300.0 volts dc blank         Thread Size:         0.250 inches         Body Material:         Metal         Maximum Dielectric Withstanding Dc Voltage:         600.0 vo	Body Length:
Narosiana Same Same Same Same Same Same Same Sam	1.020 inches
Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: N/a	Body Outside Diameter:
<pre>+10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a</pre>	0.375 inches
Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Power Line Frequency Rating Per Function In Hertz:         400.0 blank         Operating Current Rating Per Function In Amps:         0.25 blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         15.0 volts ac blank and 300.0 volts dc blank         Thread Size:         0.250 inches         Body Material:         Metal         Maximum Dielectric Withstanding Dc Voltage:         600.0 volts at sea level         Style Designator:         Round terminal/terminals on opposite surfaces         Shelf Life:         N/a	Vibration Resistance Range In Hertz:
<ul> <li>-55.0/+125.0 degrees celsius</li> <li>Source Impedance Rating Per Function:</li> <li>50.0 ohms blank</li> <li>Load Impedance Per Function:</li> <li>50.0 ohms blank</li> <li>Power Line Frequency Rating Per Function In Hertz:</li> <li>400.0 blank</li> <li>Operating Current Rating Per Function In Amps:</li> <li>0.25 blank</li> <li>Principal Circuitry Type Per Function:</li> <li>Inductance-capacitance blank</li> <li>Mounting Facility Screw Thread Series Designator:</li> <li>Unf</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 300.0 volts dc blank</li> <li>Thread Size:</li> <li>0.250 inches</li> <li>Body Material:</li> <li>Metal</li> <li>Maximum Dielectric Withstanding Dc Voltage:</li> <li>600.0 volts at sea level</li> <li>Style Designator:</li> <li>Round terminal/terminals on opposite surfaces</li> <li>Shelf Life:</li> <li>N/a</li> </ul>	+10.0/+2000.0
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Operating Tempurature Range:
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	-55.0/+125.0 degrees celsius
Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Source Impedance Rating Per Function:
50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:0.25 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 300.0 volts dc blankThread Size:0.250 inchesBody Material:MetalMaximum Dielectric Withstanding Dc Voltage:600.0 volts at sea levelStyle Designator:Round terminal/terminals on opposite surfacesShelf Life:N/a	Load Impedance Per Function:
400.0 blank Operating Current Rating Per Function In Amps: 0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	50.0 ohms blank
Operating Current Rating Per Function In Amps:         0.25 blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         115.0 volts ac blank and 300.0 volts dc blank         Thread Size:         0.250 inches         Body Material:         Metal         Maximum Dielectric Withstanding Dc Voltage:         600.0 volts at sea level         Style Designator:         Round terminal/terminals on opposite surfaces         Shelf Life:         N/a	Power Line Frequency Rating Per Function In Hertz:
0.25 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	400.0 blank
Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Operating Current Rating Per Function In Amps:
Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	0.25 blank
Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Principal Circuitry Type Per Function:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Inductance-capacitance blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Mounting Facility Screw Thread Series Designator:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Unf
Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Inclosure Type:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Hermetically sealed
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Mounting Facility Type And Quantity:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	1 threaded bushing
Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Functional Terminal Type And Quantity:
115.0 volts ac blank and 300.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	1 tab, solder lug output 2nd function
Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Operating Voltage Rating And Type Per Function:
0.250 inches <b>Body Material:</b> Metal <b>Maximum Dielectric Withstanding Dc Voltage:</b> 600.0 volts at sea level <b>Style Designator:</b> Round terminal/terminals on opposite surfaces <b>Shelf Life:</b> N/a	115.0 volts ac blank and 300.0 volts dc blank
Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Thread Size:
Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	0.250 inches
Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Body Material:
600.0 volts at sea level <b>Style Designator:</b> Round terminal/terminals on opposite surfaces <b>Shelf Life:</b> N/a	Metal
Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Maximum Dielectric Withstanding Dc Voltage:
Round terminal/terminals on opposite surfaces Shelf Life: N/a	600.0 volts at sea level
Shelf Life: N/a	Style Designator:
N/a	Round terminal/terminals on opposite surfaces
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

---



Demilitarization:

Yes - demil/mli

Fiig:

A047b0