

View Online at <https://aerobasegroup.com/nsn/5915-01-251-0031>

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**End Application:**

5865-01-145-4898 processing group

**Reference Frequency Per Function:**

126.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

108.00 megahertz blank and 123.00 megahertz blank and 129.00 megahertz blank and 154.00 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

123.00 megahertz blank and 129.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

50.0 blank and 3.0 blank and 3.0 blank and 52.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

123.0 megahertz blank and 129.0 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0