

View Online at <https://aerobasegroup.com/nsn/5915-01-252-2928>

**Overall Length:**

8.399 inches

**Body Length:**

6.400 inches

**Body Outside Diameter:**

Between 2.126 inches and 2.268 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**End Application:**

Countermeasures set an/slq-33

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

60.0 blank

**Operating Current Rating Per Function In Amps:**

30.0 blank

**Maximum Voltage Drop Per Function:**

4.5 volts ac blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

40.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

3.0 and 50.0 and 100.0 and 100.0 and 90.0 and 90.0

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

1 tab w/screw input 1st function1 tab w/screw output 2nd function

**Operating Voltage Rating And Type Per Function:**

450.0 volts ac blank

**Thread Size:**

1.125 inches

**Maximum Dielectric Withstanding Dc Voltage:**

1.0 kilovolts at sea level

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0