

View Online at <https://aerobasegroup.com/nsn/5915-01-252-2928>

Overall Length:

8.399 inches

Body Length:

6.400 inches

Body Outside Diameter:

Between 2.126 inches and 2.268 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

Countermeasures set an/slq-33

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

60.0 blank

Operating Current Rating Per Function In Amps:

30.0 blank

Maximum Voltage Drop Per Function:

4.5 volts ac blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

40.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

3.0 and 50.0 and 100.0 and 100.0 and 90.0 and 90.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 tab w/screw input 1st function1 tab w/screw output 2nd function

Operating Voltage Rating And Type Per Function:

450.0 volts ac blank

Thread Size:

1.125 inches

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0