

View Online at <https://aerobasegroup.com/nsn/5915-01-252-3206>

**Overall Height:**

1.300 inches

**Body Length:**

4.010 inches

**Body Width:**

2.750 inches

**Body Height:**

0.800 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.410 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.150 inches

**Operating Temperature Range:**

-0.0/+70.0 degrees celsius

**End Application:**

Hf-8054a rece

**Reference Frequency Per Function:**

448.325 kilohertz blank

**Source Impedance Rating Per Function:**

2.0 kilohms blank

**Load Impedance Per Function:**

2.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

8.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

446.45 kilohertz blank and 446.90 kilohertz blank and 449.75 kilohertz blank and 450.25 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

446.90 kilohertz blank and 449.75 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0