

View Online at <https://aerobasegroup.com/nsn/5915-01-252-3206>

Overall Height:

1.300 inches

Body Length:

4.010 inches

Body Width:

2.750 inches

Body Height:

0.800 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.410 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.150 inches

Operating Temperature Range:

-0.0/+70.0 degrees celsius

End Application:

Hf-8054a rece

Reference Frequency Per Function:

448.325 kilohertz blank

Source Impedance Rating Per Function:

2.0 kilohms blank

Load Impedance Per Function:

2.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

446.45 kilohertz blank and 446.90 kilohertz blank and 449.75 kilohertz blank and 450.25 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

446.90 kilohertz blank and 449.75 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0