## NSN 5915-01-252-3208

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-252-3208

Overall Length:
1.080 inches
Body Length:
0.900 inches
Body Width:
1.000 inches
Body Height:
0.230 inches
Unthreaded Mounting Hole Diameter:
0.068 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.780 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.880 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Average Life Rating In Hours:
4000.0
Reference Frequency Per Function:
27.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
20.00 megahertz blank and 24.00 megahertz blank and 30.00 megahertz blank and 35.00 megahertz blank
Body Material:

Metal

## NSN 5915-01-252-3208

Band Pass Filter - Page 2 of 2



## **Frequency Band Width Per Function:**

24.00 megahertz blank and 30.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

25.0 blank and 1.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:** 

24.0 megahertz blank and 30.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0