

View Online at <https://aerobasegroup.com/nsn/5915-01-252-3213>

Overall Length:

1.460 inches

Body Length:

1.100 inches

Body Width:

0.400 inches

Body Height:

0.220 inches

Unthreaded Mounting Hole Diameter:

0.080 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.300 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Average Life Rating In Hours:

4000.0

Reference Frequency Per Function:

1.392 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.328 gigahertz blank and 1.3915 gigahertz blank and 1.3925 gigahertz blank and 1.456 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.3915 gigahertz blank and 1.3925 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

33.0 blank and 3.0 blank and 3.0 blank and 33.0 blank

Body Surface Treatment:

Silver

Precious Material And Location:

Body surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0