

View Online at https://aerobasegroup.com/nsn/5915-01-252-3217

Overail Length: 6.960 inches Body Length: 5.060 inches Body Outside Diameter: 1.770 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Porting Current Rating Per Function In Amps: 20.0 blank Porting Current Rating Per Function In Amps: 20.0 blank Poincipal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 15.0 volts ac blank and 400.0 volts dc blan	
Body Length: 5.060 inches Body Outside Diameter: 1.770 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Porer Line Frequency Rating Per Function In Amps: 20.0 blank Poperating Current Rating Per Function In Amps: 20.0 blank Poincipal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threade bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank	Overall Length:
5.060 inches Body Outside Diameter: 1.770 inches Vibration Resistance Range In Hertz: 110.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Poincipal Circuitry Type Per Function In Amps: 20.0 blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	6.960 inches
Body Outside Diameter: 1.770 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Inpedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Poreting Current Rating Per Function In Amps: 20.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size:	Body Length:
1.770 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Code Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches	5.060 inches
Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Furcead Size: 0.750 inches Body Material:	Body Outside Diameter:
+10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Derating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches	1.770 inches
Operating Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:60.0 blankOperating Current Rating Per Function In Amps:20.0 blankPrincipal Circuitry Type Per Function In Amps:20.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 400.0 volts dc blankThread Size:0.750 inchesBody Material:	Vibration Resistance Range In Hertz:
 -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material: 	+10.0/+2000.0
Average Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:60.0 blankOperating Current Rating Per Function In Amps:20.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 400.0 volts dc blankThread Size:0.750 inchesBody Material:	Operating Tempurature Range:
250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Average Life Rating In Hours:
50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:60.0 blankOperating Current Rating Per Function In Amps:20.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 400.0 volts dc blankThread Size:0.750 inchesBody Material:	250.0
Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Source Impedance Rating Per Function:
50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches	50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:60.0 blankOperating Current Rating Per Function In Amps:20.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 400.0 volts dc blankThread Size:0.750 inchesBody Material:	Load Impedance Per Function:
60.0 blank Operating Current Rating Per Function In Amps: 20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	50.0 ohms blank
Operating Current Rating Per Function In Amps:20.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 400.0 volts dc blankThread Size:0.750 inchesBody Material:	Power Line Frequency Rating Per Function In Hertz:
20.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	60.0 blank
Principal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 400.0 volts dc blankThread Size:0.750 inchesBody Material:	Operating Current Rating Per Function In Amps:
Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	20.0 blank
Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Principal Circuitry Type Per Function:
Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Inductance-capacitance blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Mounting Facility Screw Thread Series Designator:
Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Unef
Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Inclosure Type:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Encased
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Mounting Facility Type And Quantity:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	1 threaded bushing
Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	Functional Terminal Type And Quantity:
115.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.750 inches Body Material:	1 tab, solder lug output 2nd function
Thread Size: 0.750 inches Body Material:	Operating Voltage Rating And Type Per Function:
0.750 inches Body Material:	115.0 volts ac blank and 400.0 volts dc blank
Body Material:	Thread Size:
-	0.750 inches
Metal	Body Material:
	Metal
Style Designator:	Style Designator:
Round terminal/terminals on opposite surfaces	Round terminal/terminals on opposite surfaces
Shelf Life:	Shelf Life:
N/a	N/a
	Unit Of Measure:
	Unit Of Measure:



Demilitarization:

No

Fiig:

A047b0