

View Online at <https://aerobasegroup.com/nsn/5915-01-252-3974>

**Overall Length:**

1.230 inches

**Body Length:**

0.890 inches

**Body Width:**

0.390 inches

**Body Height:**

0.230 inches

**Unthreaded Mounting Hole Diameter:**

0.068 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.890 inches

**Vibration Resistance Range In Hertz:**

+33.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.270 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

4000.0

**Reference Frequency Per Function:**

324.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Average Power Rating Per Function:**

1.0 watts blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

300.00 megahertz blank and 348.00 megahertz blank and 400.00 megahertz blank and 466.00 megahertz blank



**Body Material:**

Metal

**Frequency Band Width Per Function:**

300.00 megahertz blank and 348.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 30.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

300.0 megahertz blank and 348.0 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0