

View Online at <https://aerobasegroup.com/nsn/5915-01-252-4599>

Overall Length:

1.430 inches

Body Length:

1.250 inches

Body Width:

0.400 inches

Body Height:

0.220 inches

Unthreaded Mounting Hole Diameter:

0.080 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.150 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.300 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Average Life Rating In Hours:

4000.0

Reference Frequency Per Function:

1.325 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.2 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

7.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.20 gigahertz blank and 1.324 gigahertz blank and 1.326 gigahertz blank and 1.55 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.324 gigahertz blank and 1.326 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.324 gigahertz blank and 1.326 gigahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0