NSN 5915-01-252-6086

Band Pass Filter - Page 1 of 2

Metal



View Online at https://aerobasegroup.com/nsn/5915-01-252-6086

Overall Length:
1.280 inches
Body Length:
1.100 inches
Body Width:
0.400 inches
Body Height:
0.220 inches
Unthreaded Mounting Hole Diameter:
0.080 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.000 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.300 inches
Operating Tempurature Range:
-54.0/+85.0 degrees celsius
Average Life Rating In Hours:
4000.0
Reference Frequency Per Function:
256.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
1.2 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
4.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
192.00 megahertz blank and 251.00 megahertz blank and 261.00 megahertz blank and 320.00 megahertz blank
Body Material:
Motol

NSN 5915-01-252-6086

Band Pass Filter - Page 2 of 2



Frequency Band Width Per Function: 251.00 megahertz blank and 261.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 50.0 blank and 3.0 blank and 3.0 blank and 50.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 251.0 megahertz blank and 261.0 megahertz blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A047b0