

View Online at <https://aerobasegroup.com/nsn/5915-01-254-0719>

Overall Length:

4.140 inches

Overall Height:

Between 1.470 inches and 1.530 inches

Overall Width:

5.435 inches

Body Length:

Between 3.282 inches and 3.342 inches

Body Width:

Between 3.845 inches and 3.905 inches

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.146 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.735 inches and 3.765 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.000 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 1st radio interference 400.0 2nd radio interference

Operating Current Rating Per Function In Amps:

20.0 1st radio interference 20.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.25 volts ac 1st radio interference 1.25 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

20.0 and 30.0 and 55.0 and 65.0 and 70.0 and 70.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

2 threaded stud input 1st function 2 threaded stud output 2nd function 1 threaded stud ground 3rd function

Operating Voltage Rating And Type Per Function:

125.0 volts ac 1st radio interference 1st function 125.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.45 kilovolts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0