

View Online at <https://aerobasegroup.com/nsn/5915-01-254-2120>

Overall Length:

2.260 inches

Body Length:

1.500 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.900 inches

Vibration Resistance Range In Hertz:

+5.0/+1000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.550 inches

Operating Temperature Range:

-20.0/+50.0 degrees celsius

End Application:

Dn16208-1

Reference Frequency Per Function:

9.3 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

50140

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

50140

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

15.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

9.15 gigahertz blank and 9.275 gigahertz blank and 9.325 gigahertz blank and 9.45 gigahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

9.275 gigahertz blank and 9.325 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

42.0 blank and 3.0 blank and 3.0 blank and 42.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

9.275 gigahertz blank and 9.325 gigahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0