

View Online at <https://aerobasegroup.com/nsn/5915-01-255-8696>

Overall Length:

3.750 inches

Overall Height:

4.750 inches

Body Length:

3.000 inches

Body Width:

7.000 inches

Body Height:

4.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.187 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.375 inches

Operating Temperature Range:

+32.0/+122.0 degrees fahrenheit

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

15.0 1st radio interference 15.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.0 volts ac 1st radio interference 1.0 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Input Terminal Manufacturer Code:

53711

Input Terminal Identification:

Ms3400d22-22p

Maximum Temperature Rise:

25.0 degrees celsius

Average Power Rating Per Function:

2.015 kilowatts 1st radio interference 2.015 kilowatts 2nd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

20.0 and 60.0 and 80.0 and 80.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

6 threaded hole

Features Provided:

Moisture resistant and shock resistant

Functional Terminal Type And Quantity:

1 connector, plug input 1st function 2 threaded stud output 2nd function 1 threaded stud ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

1.0 kilovolts at sea level

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function 115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.164 inches

Body Material:

Metal

Special Features:

Two filtered functions

Unpackaged Unit Weight:

7.000 pounds

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0