

View Online at <https://aerobasegroup.com/nsn/5915-01-257-3478>

Overall Length:

13.125 inches

Mounting Slot Width:

0.300 inches

Body Length:

12.000 inches

Body Width:

3.000 inches

Body Height:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.000 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

5805-01-245-9058 small extension

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

60.0 blank

Operating Current Rating Per Function In Amps:

40.0 blank

Maximum Voltage Drop Per Function:

1.25 volts ac blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

38.0 and 80.0 and 80.0 and 80.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud4 slot

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 threaded stud input 1st function1 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank

Thread Size:

0.375 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

800.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0