

View Online at <https://aerobasegroup.com/nsn/5915-01-257-3478>

**Overall Length:**

13.125 inches

**Mounting Slot Width:**

0.300 inches

**Body Length:**

12.000 inches

**Body Width:**

3.000 inches

**Body Height:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.000 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.000 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**End Application:**

5805-01-245-9058 small extension

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

60.0 blank

**Operating Current Rating Per Function In Amps:**

40.0 blank

**Maximum Voltage Drop Per Function:**

1.25 volts ac blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

38.0 and 80.0 and 80.0 and 80.0 and 80.0 and 80.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud4 slot

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

1 threaded stud input 1st function1 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank

**Thread Size:**

0.375 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

800.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0