NSN 5915-01-260-2736

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-260-2736

Overall Length:

Between 2.970 inches and 3.030 inches

Overall Height:

Between 7.380 inches and 7.560 inches

Body Length:

Between 1.970 inches and 2.030 inches

Body Width:

Between 1.970 inches and 2.030 inches

Body Height:

Between 6.160 inches and 6.280 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.490 inches and 2.510 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.990 inches and 1.010 inches

Operating Tempurature Range:

-40.0/+71.0 degrees celsius

Reference Frequency Per Function:

4.6 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

94990

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

94990

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.6 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

NSN 5915-01-260-2736

Band Pass Filter - Page 2 of 2

A047b0



Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.6 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
4.283 gigahertz blank and 4.40 gigahertz blank and 4.80 gigahertz blank and 4.917 gigahertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
4.40 gigahertz blank and 4.80 gigahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
30.0 blank and 3.0 blank and 30.0 blank
Voltage Standing Wave Ratio Frequency Limits Per Function:
4.4 gigahertz blank and 4.8 gigahertz blank
Style Designator:
Rectangular terminal/terminals on three surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: