## NSN 5915-01-260-2736

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-260-2736

**Overall Length:** 

Between 2.970 inches and 3.030 inches

**Overall Height:** 

Between 7.380 inches and 7.560 inches

**Body Length:** 

Between 1.970 inches and 2.030 inches

**Body Width:** 

Between 1.970 inches and 2.030 inches

**Body Height:** 

Between 6.160 inches and 6.280 inches

**Unthreaded Mounting Hole Diameter:** 

0.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

Between 2.490 inches and 2.510 inches

**Vibration Resistance Range In Hertz:** 

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.990 inches and 1.010 inches

**Operating Tempurature Range:** 

-40.0/+71.0 degrees celsius

**Reference Frequency Per Function:** 

4.6 gigahertz blank

**Source Impedance Rating Per Function:** 

50.0 ohms blank

**Load Impedance Per Function:** 

50.0 ohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

**Input Terminal Manufacturer Code:** 

94990

**Input Terminal Identification:** 

Sma-receptacle

**Output Terminal Manufacturer Code:** 

94990

**Output Terminal Identification:** 

Sma-receptacle

**Voltage Standing Wave Ratio Per Function:** 

1.6 blank

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Inclosure Type:** 

Encased

## NSN 5915-01-260-2736

Band Pass Filter - Page 2 of 2

A047b0



| Mounting Facility Type And Quantity:  |
|---|
| 4 unthreaded hole   |
| Insertion Loss At Reference Frequency Per Function In Decibels:                                   |
| 1.6 blank   |
| Functional Terminal Type And Quantity:  |
| 1 connector, receptacle output 2nd function   |
| Specified Frequencies Of Discrimination Per Function:   |
| 4.283 gigahertz blank and 4.40 gigahertz blank and 4.80 gigahertz blank and 4.917 gigahertz blank |
| Thread Size:  |
| 0.112 inches  |
| Body Material:  |
| Metal   |
| Frequency Band Width Per Function:  |
| 4.40 gigahertz blank and 4.80 gigahertz blank   |
| Discrimination At Specificationified Frequencies Per Function In Decibels:                        |
| 30.0 blank and 3.0 blank and 30.0 blank   |
| Voltage Standing Wave Ratio Frequency Limits Per Function:  |
| 4.4 gigahertz blank and 4.8 gigahertz blank   |
| Style Designator:   |
| Rectangular terminal/terminals on three surfaces  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |