

View Online at <https://aerobasegroup.com/nsn/5915-01-260-9432>

**Overall Height:**

7.842 inches

**Body Length:**

4.160 inches

**Body Width:**

2.530 inches

**Body Height:**

6.030 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.625 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.010 inches

**Operating Temperature Range:**

-0.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Source Impedance Rating Per Function:**

50.0 ohms 3rd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 3rd radio interference

**Operating Current Rating Per Function In Amps:**

15.0 3rd radio interference

**Maximum Voltage Drop Per Function:**

1.15 volts ac 3rd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference

**Input Terminal Manufacturer Code:**

71468

**Input Terminal Identification:**

Gs02-18-11p

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Functional Terminal Type And Quantity:**

3 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

208.0 volts ac 3rd radio interference 3rd function

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1.0 kilovolts at sea level

**Unpackaged Unit Weight:**

6.000 pounds

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0