

View Online at <https://aerobasegroup.com/nsn/5915-01-262-1718>

**Overall Height:**

0.500 inches

**Body Length:**

3.380 inches

**Body Width:**

0.380 inches

**Body Height:**

0.380 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.180 inches

**Operating Temperature Range:**

-46.0/+75.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

640.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

600.00 megahertz blank and 639.00 megahertz blank and 641.00 megahertz blank and 680.00 megahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Aluminum

**Frequency Band Width Per Function:**

639.00 megahertz blank and 641.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

80.0 blank and 5.0 blank and 5.0 blank and 80.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

639.0 megahertz blank and 641.0 megahertz blank

**Precious Material And Location:**

Terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0